

EXTERIOR MDF - SPECIFICATION SHEET

Gen-Eco Exterior MDF is a medium-density fibreboard (MDF) made from select wooden fibres. These fibres are bound with formaldehyde-free (E0) PMDI glues under high pressure and temperature.

CHARACTERISTICS

Gen-Eco Exterior MDF complies with the V100 testing method (defined in standard EN 1087-1). It is suitable for use in Classes of Risk 1, 2 and 3, as defined by standard EN 335-3.

Key characteristics include:

- High resistance to humidity
- Low swelling in extreme humidity
- Dimensional stability
- Water resistance

APPLICATIONS

Gen-Eco Exterior MDF is ideal for a number of exterior and interior applications, including:

- Outdoor kitchens
- Outdoor furniture
- Exterior wall and ceiling linings
- Exterior doors
- Flooring
- Skirting
- Window framing

BENEFITS

Gen-Eco Exterior MDF is ideal for exterior use when installed 100mm above the ground. The faces and edges need to be coated with an exterior paint, preferably a 2 pack system. It can also be used for interiors which separate environments, such as laundries and bathrooms.

WARRANTY

Gen-Eco Exterior MDF comes with a seven-year warranty which is valid for products installed within our height guidelines (at least 100mm above ground) and are suitably coated with a protective finish.

FINISHES

Gen-Eco Exterior MDF can be supplied either raw or with a white two-sides melamine finish.

SHEET SIZES

- 2440 x 1220 x 16mm
- 2440 x 1220 x 18mm

